

What is claimed is:

CLAIMS

1 1. A tray retainer for holding a tray stack having a plurality of trays that
2 are configured to carry microelectronic devices, comprising:

3 a guide structure having a first region, a second region spaced apart from
4 the first region, a first channel section extending in a direction of a load/unload path
5 between the first and second regions, and a second channel section extending in the
6 direction of the load/unload path between the first and second regions, the second channel
7 section facing the first channel section;

8 a cross-member extending transverse to the load/unload path and at least
9 partially across the first region of the guide structure between the first and second channel
10 sections; and

11 a moveable retaining element positioned at the second region of the guide
12 structure, the retaining element being moveable to a storage position in which the
13 retaining element projects a first distance transverse to the load/unload path into the guide
14 structure, and the retaining element being moveable to a load/unload position in which
15 the retaining element either does not project into the retaining assembly or projects a
16 second distance less than the first distance.

17 2. The tray retainer of claim 1 wherein:

18 the guide structure comprises a frame having a bearing plate with a first end
19 and a second end, a plurality of elongated L-shaped channel members attached to the first
20 and second ends of the bearing plate, and panels attached to the channel members and/or
the bearing plate, the channel members including first and second channel members
attached to the first end of the bearing plate defining the first channel section and third
and fourth channel members attached to the second end of the bearing plate defining the
second channel section, wherein the channel members project from the bearing plate in
the direction of the load/unload path, and wherein the first channel member faces the
third channel member and the second channel member faces the fourth channel member;

the tray retainer further includes a lock/release mechanism coupled to the guide structure, the cross-member and the retaining element, the lock/release mechanism including at least one shaft coupled to the retaining element, an actuator coupled to the shaft, and a lock bearing coupled to the cross-member, the shaft having a sleeve with a contact portion, a bore and a slot, and the shaft also having a through-pin slidably received in the bore of the sleeve, and the shaft further having a key attached to the through-pin and received slot of the sleeve, the key rotating the sleeve with rotation of the through-pin, the actuator having a pulley attached to one end of the through pin, a drive cylinder and a belt engaging the drive cylinder and the pulley, and the lock bearing having a resilient engagement member to selectively engage the contact portion of the sleeve, wherein an operator rotates the drive shaft to rotate the through-pin, sleeve and retaining element between the storage position and the load/unload position; and the cross-member comprises a moveable plate.

3. The tray retainer of claim 1 wherein the guide structure comprises a frame having a bearing plate with a first end and a second end, a plurality of elongated L-shaped channel members attached to the first and second ends of the bearing plate, and panels attached to the channel members and/or the bearing plate, the channel members including first and second channel members attached to the first end of the bearing plate defining the first channel section and third and fourth channel members attached to the second end of the bearing plate defining the second channel section, wherein the channel members project from the bearing plate in the direction of the load/unload path, and the first channel member faces the third channel member and the second channel member faces the fourth channel member.

4. The tray retainer of claim 1 wherein:
the first channel section comprises a first C-shaped channel member, and
the second channel section comprises a second C-shaped channel member; and

4 the cross-member comprises a plate having a first end attached to the first
5 C-shaped channel member and a second end attached to the second C-shaped channel
6 member.

1 5. The tray retainer of claim 1 wherein:
2 the first channel section comprises a first C-shaped channel member, and
3 the second channel section comprises a second C-shaped channel member;
4 the cross-member comprises a floating plate extending at least partially
5 between the first C-shaped channel member and the second C-shaped channel member,
6 the floating plate being moveable along the load/unload path; and
7 the retaining element comprises a tab projecting into a cavity between the
8 first and second C-shaped channel members in the storage position.

1 6. The tray retainer of claim 1 wherein:
2 the first channel section comprises first and second L-shaped channel
3 members, and the second channel section comprises third and fourth L-shaped channel
4 members; and
5 the cross-member comprises a plate having a first end attached to the first
6 and second L-shaped channel members and a second end attached to the third and fourth
7 L-shaped channel members.

1 7. The tray retainer of claim 1 wherein:
2 the first channel section comprises first and second L-shaped channel
3 members, and the second channel section comprises third and fourth L-shaped channel
4 members;
5 the cross-member comprises a floating plate extending at least partially
6 between the first L-shaped channel member, the second L-shaped channel member, the
7 third L-shaped channel member, and the fourth L-shaped channel member, the floating
8 plate being moveable along the load/unload path; and

9 the retaining element comprises a tab projecting into a cavity between the
10 first and second L-shaped channel members in the storage position.

1 8. The tray retainer of claim 1 wherein:
2 the guide structure comprises a unitary shell, and the first channel section is
3 defined by a first end of the shell and the second channel section is defined by a second
4 end of the shell; and
5 the cross-member comprises a plate attached to the shell.

1 9. The tray retainer of claim 1, further comprising a lock/release
2 mechanism having an actuator, a shaft having a first end coupled to the retaining element
3 and a second end coupled to the actuator, and a lock bearing attached to the cross-
4 member and slidably receiving the shaft, the actuator rotating to rotate the retaining
5 element between the storage position and the load/unload position and to rotate the shaft
6 between a lock position and a release position relative to the lock bearing, the lock
7 bearing preventing the cross-member from moving along the shaft when the shaft is in the
8 lock position and the retaining element is in the storage position, and the lock bearing
9 allowing the cross-member to move along the shaft when the shaft is in the release
10 position and the retaining element is in the load/unload position.

1 10. The tray retainer of claim 1, further comprising a lock/release
2 mechanism having an actuator and a shaft coupled to the actuator, the actuator having a
3 drive cylinder and a belt contacting the drive cylinder, and the shaft having a through-pin
4 including a first end coupled to the belt and a second end attached to the retaining
5 element, a key attached to the through-pin proximate to the second end, and a sleeve
6 having a bore receiving the through-pin and a slot receiving the key, wherein rotation of
7 the drive cylinder rotates the through-pin and the sleeve to move the shaft between a lock
8 position in which the retaining element is in the storage position and a release position in
9 which the retaining element is in the load/unload position.

11. The tray retainer of claim 1 wherein:

the guide structure comprises a frame having a bearing plate and a plurality of channel members including at least a first channel member projecting from one end of the bearing plate and a second channel member projecting from another end of the bearing plate, the first channel member defining the first channel section of the guide structure and the second channel member defining the second channel section of the guide structure;

the retaining element comprises a tab; and

the tray retainer further comprising a lock/release mechanism having an actuator, a shaft coupled to the actuator, and a lock bearing slidably receiving the shaft and attached to the cross-member, wherein movement of the actuator to a first position moves shaft to a lock position in which the lock bearing engages the shaft to prevent the cross-member from moving along the shaft and in which the tab projects into a space between the first and second channel members in the storage position, and wherein movement of the actuator to a second position moves the shaft to a release position in which lock bearing disengages the shaft to allow the cross-member to move along the shaft and in which the tab is at least partially removed from the space between the first and second channel members in the load/unload position.

12. The tray retainer of claim 1, further comprising a lock/release assembly including:

a lock bearing attached to the cross-member, the lock bearing having a hole;

a shaft extending in the direction of the load/unload path, the shaft being slidably and rotatably received in the hole of the lock bearing, wherein at least one of the lock bearing and the shaft rotates between a lock position and a release position; and

an engagement assembly having an engagement element, a contact surface and a release surface, the engagement element being coupled to one of the shaft or the lock bearing, and the contact surface and the release surface being on the other of the shaft or the lock bearing, the contact surface being configured to contact the engagement

11 element and prevent axial movement between the lock bearing and the shaft in the lock
12 position, and the release surface being configured to be spaced apart from the engagement
13 element and allow axial movement between the lock bearing and the shaft in the release
14 position.

1 13. The tray retainer of claim 12 wherein:

2 the shaft comprises a contoured elongated member having a flat section
3 defining the release surface and a rounded outer section defining the contact surface, the
4 rounded outer section having a curved outer surface with a diameter to fit within the hole
5 of the lock bearing; and

6 the lock bearing comprises a hub having a cylindrical hole, an interior
7 groove with in the hole, and a resilient member defining the engagement member in the
8 groove, the flat section being juxtaposed to the resilient member in the release position
9 and the outer section contacting the resilient member in the lock position.

1 14. The tray retainer of claim 12 wherein:

2 the shaft comprises an elongated member having a flat section defining the
3 release surface and a plurality of truncated annular teeth defining the contact surface; and

4 the lock bearing comprises a hub having a cylindrical hole, a flat portion,
5 and a slot in the flat portion defining the engagement element, the flat section of the shaft
6 being juxtaposed to the flat portion of the lock bearing in the release position and at least
7 one of the annular teeth being in the slot in the lock position.

1 15. A retainer for holding a tray stack having a plurality of trays
2 configured to carry a plurality of microelectronic devices, comprising:

3 a casing having a guide structure with a first end, a second end, an interior
4 holding area, and an opening at the second end of the guide structure for receiving the
5 trays, the guide structure being configured to receive the tray stack and allow the tray
6 stack to move along a load/unload path through the guide structure;

7 a cross-member member extending across at least a portion of the casing
8 transverse to the load/unload path, the cross-member being spaced apart from the second
9 end of the casing; and

10 a plurality of moveable retaining elements at least proximate to the second
11 end, the retaining elements being moveable between a storage position in which the
12 retaining elements project into the interior holding area of the guide structure to obstruct
13 the load/unload path, and the retaining elements being moveable into a load/unload
14 position in which the retaining elements are clear the load/unload path.

1 16. The retainer of claim 15 wherein:
2 the guide structure has a first channel section comprising a first C-shaped
3 channel member and a second channel section comprising second C-shaped channel
4 member; and

5 the cross-member comprises a plate having a first end attached to the first
6 C-shaped channel member and a second end attached to the second C-shaped channel
7 member.

8 17. The retainer of claim 15 wherein:
9 the guide structure has a first channel section comprising a first C-shaped
10 channel member and a second channel section comprising a second C-shaped channel
11 member;

12 the cross-member comprises a floating plate extending at least partially
13 between the first C-shaped channel member and the second C-shaped channel member,
14 the floating plate being moveable along the load/unload path; and

15 the retaining element comprises a tab projecting into a cavity between the
16 first and second C-shaped channel members in the storage position.

1 18. The retainer of claim 15 wherein:

2 the guide structure has a first channel section comprising first and second
3 L-shaped channel members and a second channel section comprising third and fourth L-
4 shaped channel members; and

5 the cross-member comprises a plate having a first end attached to the first
6 and second L-shaped channel members and a second end attached to the third and fourth
7 L-shaped channel members.

1 19. The retainer of claim 15 wherein:

2 the guide structure has a first channel section comprising first and second
3 L-shaped channel members and a second channel section comprising third and fourth L-
4 shaped channel members;

5 the cross-member comprises a floating plate extending at least partially
6 between the first L-shaped channel member, the second L-shaped channel member, the
7 third L-shaped channel member, and the fourth L-shaped channel member, the floating
8 plate being moveable along the load/unload path; and

9 the retaining element comprises a tab projecting into a cavity between the
10 first and second L-shaped channel members in the storage position.

1 20. The retainer of claim 15, further comprising a lock/release assembly
2 including:

3 a lock bearing attached to the cross-member, the lock bearing having a hole;
4 a shaft extending in the direction of the load/unload path, the shaft being
5 slidably and rotatably received in the hole of the lock bearing, wherein at least one of the
6 lock bearing and the shaft rotates between a lock position and a release position; and

7 an engagement assembly having an engagement element, a contact surface
8 and a release surface, the engagement element being coupled to one of the shaft or the
9 lock bearing, and the contact surface and the release surface being on the other of the
10 shaft or the lock bearing, the contact surface being configured to contact the engagement

11 element and prevent axial movement between the lock bearing and the shaft in the lock
12 position, and the release surface being configured to be spaced apart from the engagement
13 element and allow axial movement between the lock bearing and the shaft in the release
14 position.

1 21. A retainer for holding a tray stack having a plurality of trays that are
2 configured to carry microelectronic devices, comprising:

3 a protective casing including a guide structure having a first guide section
4 configured to receive a first side of the tray stack, a second guide section configured to
5 receive a second side of the tray stack, the first and second guide sections defining an
6 opening and an interior holding area configured to retain the tray stack in a stacked
7 arrangement and to allow the tray stack to move through the guide structure;

8 a cross-member extending at least partially between the first and second
9 guides sections; and

10 a plurality of moveable retaining elements in the casing at least proximate
11 to the opening, the retaining elements being moveable between a storage position in
12 which the retaining elements project into the opening and a load/unload position in which
13 the retaining elements either do not project as far into the opening or are completely
14 removed from the opening.

1 22. The retainer of claim 21 wherein:

2 the first channel section comprises a first C-shaped channel member, and
3 the second channel section comprises a second C-shaped channel member; and

4 the cross-member comprises a plate having a first end attached to the first
5 C-shaped channel member and a second end attached to the second C-shaped channel
6 member.

1 23. The retainer of claim 21 wherein:
2 the first channel section comprises first and second L-shaped channel
3 members, and the second channel section comprises third and fourth L-shaped channel
4 members; and
5 the cross-member comprises a plate having a first end attached to the first
6 and second L-shaped channel members and a second end attached to the third and fourth
7 L-shaped channel members.

1 24. The retainer of claim 21, further comprising a lock/release assembly
2 including:
3 a lock bearing attached to the cross-member, the lock bearing having a hole;
4 a shaft extending in the direction of the load/unload path, the shaft being
5 slidably and rotatably received in the hole of the lock bearing, wherein at least one of the
6 lock bearing and the shaft rotates between a lock position and a release position; and
7 an engagement assembly having an engagement element, a contact surface
8 and a release surface, the engagement element being coupled to one of the shaft or the
9 lock bearing, and the contact surface and the release surface being on the other of the
10 shaft or the lock bearing, the contact surface being configured to contact the engagement
11 element and prevent axial movement between the lock bearing and the shaft in the lock
12 position, and the release surface being configured to be spaced apart from the engagement
13 element and allow axial movement between the lock bearing and the shaft in the release
14 position.

1 25. A retainer for holding a tray stack having a plurality of trays that are
2 configured to carry microelectronic devices, comprising:
3 a housing having a frame and a plurality of panels attached to the frame, the
4 frame including a first guide having an interior structure configured to moveably retain a
5 first side of the tray stack, a second guide having an inner structure configured to
6 moveably retain a second side of the tray stack, a bearing plate attached to an upper

7 section of the first and second guides to fix together the first and second guides, the
8 panels being attached to the frame to define a cavity configured to receive the tray stack,
9 and the panels defining an opening to the cavity opposite of the bearing plate through
10 which the tray stack can pass into or out of the housing;

11 a quick release lock assembly coupled to the housing, the lock assembly
12 having an actuator, a plurality of shafts coupled to the actuator and positioned in the
13 housing to move between a first position and second position, and a retaining element
14 attached to an end of each shaft at least proximate to the opening of the housing, the
15 retaining elements moving with the shafts between a storage position when the shafts are
16 in the first position and a load/unload position when the shafts are in the second position,
17 wherein the retaining elements at least partially obstruct the opening in the storage
18 position to hold trays of the tray stack in the housing, and the retaining elements do not
19 obstruct the opening in the load/unload position to allow individual trays to pass through
20 the opening; and

21 a floating plate slidably attached to the shafts, the floating plate driving the
22 trays towards the opening when the retaining elements are in the load/unload position.

26. The retainer of claim 25 wherein the quick release lock assembly
2 further comprises a plurality of lock bearings attached to the floating plate, the lock
3 bearings each having a hole, and wherein the shafts extend in the direction of the
4 load/unload path and each shaft is slidably and rotatably received in a hole of a
5 corresponding lock bearing, wherein at least one of the lock bearings and the shafts rotate
6 between a lock position and a release position.

1 27. The retainer of claim 26 wherein the lock bearing each further
2 comprise an engagement assembly having an engagement element, a contact surface and a
3 release surface, the engagement element being coupled to one of the shafts or the lock
4 bearings, and the contact surface and the release surface being on the other of the shafts
5 or the lock bearings.

1 28. The retainer of claim 27 wherein the contact surface is configured to
2 contact the engagement element and prevent axial movement between the lock bearing
3 and the shaft in the lock position, and the release surface is configured to be spaced apart
4 from the engagement element and allow axial movement between the lock bearing and
5 the shaft in the release position.

1 29. The retainer of claim 28 wherein:
2 the shafts each comprise a contoured elongated member having a flat
3 section defining the release surface and a rounded outer section defining the contact
4 surface, the rounded outer section having a curved outer surface with a diameter to fit
5 within the hole of a corresponding lock bearing; and

6 the lock bearings each comprise a hub having a cylindrical hole, an interior
7 groove within the hole, and a resilient member defining the engagement member in the
8 groove, the flat section of a shaft being juxtaposed to the resilient member of a
9 corresponding lock bearing in the release position and the outer section of the shaft
10 contacting the resilient member of the corresponding lock bearing in the lock position.

1 30. The retainer of claim 28 wherein:
2 the shafts each comprise an elongated member having a flat section defining
3 the release surface and a plurality of truncated annular teeth defining the contact surface;
4 and

5 the lock bearings each comprise a hub having a hole, a flat portion, and a
6 slot in the flat portion defining the engagement element, the flat section of a shaft being
7 juxtaposed to the flat portion of a corresponding lock bearing in the release position and
8 at least one of the annular teeth being in the slot in the lock position.

1 31. A retainer for holding a tray stack having a plurality of trays that are
2 configured to carry microelectronic devices, comprising:

3 a casing having a guide structure with a first end and a second end, an
4 interior holding area, and an opening at least proximate to the second end, the guide
5 structure being configured to support the tray stack with respect to a load/unload path and
6 to allow the tray stack to move through the guide structure along the load/unload path;

7 a plurality of moveable retaining elements at least proximate to the second
8 end, the retaining elements being moveable between a storage position in which the
9 retaining elements project into the interior holding area of the guide structure and a
10 load/unload position in which the retaining elements either do not project as far into the
11 interior holding area or are completely removed from the interior holding area; and

12 a floating plate moveably positioned in the casing to move along the
13 load/unload path defined by the guide structure, the floating plate pushing the trays
14 against the retaining elements when the retaining elements are in the storage position and
15 the floating plate pushing the trays out of the casing when the retaining elements are in
16 the load/unload position.

17 32. The retainer of claim 31 wherein:

18 the guide structure has a first channel section comprising a first C-shaped
19 channel member and a second channel section comprising second C-shaped channel
20 member; and

21 the floating plate has a first end adjacent to the first C-shaped channel
22 member and a second end adjacent to the second C-shaped channel member.

23 33. The retainer of claim 31 wherein:

24 the guide structure has a first channel section comprising first and second
25 L-shaped channel members and a second channel section comprising third and fourth L-
26 shaped channel members; and

5 the floating plate has a first end adjacent to the first and second L-shaped
6 channel members and a second end adjacent to the third and fourth L-shaped channel
7 members.

1 34. The retainer of claim 31, further comprising a lock/release assembly
2 including:

3 a lock bearing attached to the floating plate, the lock bearing having a hole;
4 a shaft extending in the direction of the load/unload path, the shaft being
5 slidably and rotatably received in the hole of the lock bearing, wherein at least one of the
6 lock bearing and the shaft rotates between a lock position and a release position; and

7 an engagement assembly having an engagement element, a contact surface
8 and a release surface, the engagement element being coupled to one of the shaft or the
9 lock bearing, and the contact surface and the release surface being on the other of the
10 shaft or the lock bearing, the contact surface being configured to contact the engagement
11 element and prevent axial movement between the lock bearing and the shaft in the lock
position, and the release surface being configured to be spaced apart from the engagement
element and allow axial movement between the lock bearing and the shaft in the release
position.

1 35. A machine for processing microelectronic devices, comprising:
2 a receiving station having a platform with a tray singulator and a mounting
3 element;

4 a removable tray retainer configured to hold a tray stack, the tray retainer
5 having a guide structure including a first guide section and a second guide section, a
6 cross-member extending at least partially between and transverse to the first and second
7 guide sections, and a moveable retaining element spaced apart from the cross-member,
8 the retaining element being moveable between a storage position in which the retaining
9 element obstructs a load/unload path through the guide structure and a load/unload
10 position in which the retaining element does not obstruct the load/unload path and also
11 engages the mounting element to releasably hold the cassette to the platform; and

12 a processing station that processes the microelectronic devices.

1 36. The machine of claim 35 wherein the guide structure comprises a
2 frame having a bearing plate with a first end and a second end, a plurality of elongated L-
3 shaped channel members attached to the first and second ends of the bearing plate, and
4 panels attached to the channel members and/or the bearing plate, the channel members
5 including first and second channel members attached to the first end of the bearing plate
6 defining the first channel section and third and fourth channel members attached to the
7 second end of the bearing plate defining the second channel section, wherein the channel
8 members project from the bearing plate in the direction of the load/unload path, and the
9 first channel member faces the third channel member and the second channel member
10 faces the fourth channel member.

11 37. The machine of claim 35 wherein:
12 the first channel section comprises a first C-shaped channel member, and
1 the second channel section comprises a second C-shaped channel member; and
2 the cross-member comprises a plate having a first end attached to the first
3 C-shaped channel member and a second end attached to the second C-shaped channel
4 member.
5
6

1 38. The machine of claim 35 wherein:
2 the first channel section comprises a first C-shaped channel member, and
3 the second channel section comprises a second C-shaped channel member;
4 the cross-member comprises a plate having a first end attached to the first
5 C-shaped channel member and a second end attached to the second C-shaped channel
6 member; and
7 the retaining element comprises a tab projecting into a cavity between the
8 first and second C-shaped channel members in the storage position.

1 39. The machine of claim 35 wherein:
2 the first channel section comprises first and second L-shaped channel
3 members, and the second channel section comprises third and fourth L-shaped channel
4 members; and
5 the cross-member comprises a plate having a first end attached to the first
6 and second L-shaped channel members and a second end attached to the third and fourth
7 L-shaped channel members.

1 40. The machine of claim 35 wherein:
2 the first channel section comprises first and second L-shaped channel
3 members, and the second channel section comprises third and fourth L-shaped channel
4 members;
5 the cross-member comprises a plate having a first end attached to the first
6 and second L-shaped channel members and a second end attached to the third and fourth
7 L-shaped channel members; and
8 the retaining element comprises a tab projecting into a cavity between the
9 first and second L-shaped channel members in the storage position.

1 41. The machine of claim 35 wherein:
2 the guide structure comprises a unitary shell, and the first channel section is
3 defined by a first end of the shell and the second channel section is defined by a second
4 end of the shell; and
5 the cross-member comprises a plate attached to the shell.

1 42. The machine of claim 35, further comprising a lock/release
2 mechanism having an actuator, a shaft having a first end coupled to the retaining element
3 and a second end coupled to the actuator, and a lock bearing attached to the cross-
4 member and slidably receiving the shaft, the actuator rotating to rotate the retaining
5 element between the storage position and the load/unload position and to rotate the shaft

6 between a lock position and a release position relative to the lock bearing, the lock
7 bearing preventing the cross-member from moving along the shaft when the shaft is in the
8 lock position and the retaining element is in the storage position, and the lock bearing
9 allowing the cross-member to move along the shaft when the shaft is in the release
10 position and the retaining element is in the load/unload position.

1 43. The machine of claim 35, further comprising a lock/release
2 mechanism having an actuator and a shaft coupled to the actuator, the actuator having a
3 drive cylinder and a belt contacting the drive cylinder, and the shaft having a through-pin
4 including a first end coupled to the belt and a second end attached to the retaining
5 element, a key attached to the through-pin proximate to the second end, and a sleeve
6 having a bore receiving the through-pin and a slot receiving the key, wherein rotation of
7 the drive cylinder rotates the through-pin and the sleeve to move the shaft between a lock
8 position in which the retaining element is in the storage position and a release position in
9 which the retaining element is in the load/unload position.

1 44. The machine of claim 35 wherein:
2 the guide structure comprises a frame having a bearing plate and a plurality
3 of channel members including at least a first channel member projecting from one end of
4 the bearing plate and a second channel member projecting from another end of the
5 bearing plate, the first channel member defining the first channel section of the guide
6 structure and the second channel member defining the second channel section of the
7 guide structure;

8 the retaining element comprises a tab; and
9 the tray retainer further comprising a lock/release mechanism having an
10 actuator, a shaft coupled to the actuator, and a lock bearing slidably receiving the shaft
11 and attached to the cross-member, wherein movement of the actuator to a first position
12 moves shaft to a lock position in which the lock bearing engages the shaft to prevent the
13 cross-member from moving along the shaft and in which the tab projects into a space
14 between the first and second channel members in the storage position, and wherein

15 movement of the actuator to a second position moves the shaft to a release position in
16 which lock bearing disengages the shaft to allow the cross-member to move along the
17 shaft and in which the tab is at least partially removed from the space between the first
18 and second channel members in the load/unload position.

1 45. The machine of claim 35, further comprising a lock/release assembly
2 including:

3 a lock bearing attached to the cross-member, the lock bearing having a hole;
4 a shaft extending in the direction of the load/unload path, the shaft being
5 slidably and rotatably received in the hole of the lock bearing, wherein at least one of the
6 lock bearing and the shaft rotates between a lock position and a release position; and

7 an engagement assembly having an engagement element, a contact surface
8 and a release surface, the engagement element being coupled to one of the shaft or the
9 lock bearing, and the contact surface and the release surface being on the other of the
10 shaft or the lock bearing, the contact surface being configured to contact the engagement
11 element and prevent axial movement between the lock bearing and the shaft in the lock
12 position, and the release surface being configured to be spaced apart from the engagement
13 element and allow axial movement between the lock bearing and the shaft in the release
14 position.

1 46. The machine of claim 45 wherein:

2 the shaft comprises a contoured elongated member having a flat section
3 defining the release surface and a rounded outer section defining the contact surface, the
4 rounded outer section having a curved outer surface with a diameter to fit within the hole
5 of the lock bearing; and

6 the lock bearing comprises a hub having a cylindrical hole, an interior
7 groove with in the hole, and a resilient member defining the engagement member in the
8 groove, the flat section being juxtaposed to the resilient member in the release position
9 and the outer section contacting the resilient member in the lock position.

1 47. The machine of claim 45 wherein:

2 the shaft comprises an elongated member having a flat section defining the
3 release surface and a plurality of truncated annular teeth defining the contact surface; and
4 the lock bearing comprises a hub having a cylindrical hole, a flat portion,
5 and a slot in the flat portion defining the engagement element, the flat section of the shaft
6 being juxtaposed to the flat portion of the lock bearing in the release position and at least
7 one of the annular teeth being in the slot in the lock position.

1 48. A machine for processing microelectronic devices, comprising:

2 a stack of JEDEC trays, each JEDEC tray carrying a plurality of
3 microelectronic devices;

4 a receiving station having a platform with a tray singulator and a mounting
5 element, the tray singulator being configured to selectively separate and retain a single
6 JEDEC tray from the stack of JEDEC trays;

7 a portable tray retainer configured to hold the stack of JEDEC trays, the
8 tray retainer being releasably attached to the receiving station and the tray retainer
9 including a casing and a plurality of retaining elements, wherein the casing includes a
10 guide structure with a first end spaced apart from the receiving station and a second end
11 proximate to the receiving station, a cross-member extending across at least a portion of
12 the guide structure at least proximate to the first end, and an opening at least proximate to
13 the second end through which the JEDEC trays can pass into or out of the casing,
14 wherein the retaining elements are positioned proximate to the opening and are moveable
15 between a storage position and a load/unload position, the retaining elements projecting
16 into the guide structure in the storage position to hold the JEDEC trays in the retainer,
17 and at least a portion of the retaining elements projecting away from the guide structure
18 and engaging a corresponding mounting element of the receiving station in the
19 load/unload position to allow the JEDEC trays to pass through the opening and to
20 releasably hold the retainer to the receiving station, and wherein the cross-member is
21 moveably positioned in the casing to move along a load/unload path to push a bottom tray

22 of the tray stack against the retaining elements when the retaining elements are in the
23 storage position and to drive the bottom tray out of the casing to the singulator when the
24 retaining elements are in the load/unload position; and

25 a processing station that processes microelectronic devices on JEDEC trays
26 that have been unloaded from the retainer.

1 49. A lock/release assembly, comprising:

2 a lock bearing having a hole;

3 an elongated shaft slidably and rotatably received in the hole of the lock
4 bearing, wherein at least one of the lock bearing and the shaft is rotatable between a lock
5 position and a release position; and

6 an engagement assembly having an engagement element, a contact surface
7 and a release surface, the engagement element being coupled to one of the shaft or the
8 lock bearing, and the contact surface and the release surface being on the other of the
9 shaft or the lock bearing, the contact surface being configured to contact the engagement
10 element and prevent axial movement between the lock bearing and the shaft in the lock
11 position, and the release surface being configured to be spaced apart from the engagement
12 element and allow axial movement between the lock bearing and the shaft in the release
13 position.

1 50. The lock/release assembly of claim 49 wherein:

2 the shaft comprises a contoured elongated member having a flat section
3 defining the release surface and a rounded outer section defining the contact surface, the
4 rounded outer section having a curved outer surface with a diameter to fit within the hole
5 of the lock bearing; and

6 the lock bearing comprises a hub having a cylindrical hole, an interior
7 groove with in the hole, and a resilient member defining the engagement member in the
8 groove, the flat section being juxtaposed to the resilient member in the release position
9 and the outer section contacting the resilient member in the lock position.

1 51. The lock/release assembly of claim 49 wherein:
2 the shaft comprises an elongated member having a flat section defining the
3 release surface and a plurality of truncated annular teeth defining the contact surface; and
4 the lock bearing comprises a hub having a cylindrical hole, a flat portion,
5 and a slot in the flat portion defining the engagement element, the flat section of the shaft
6 being juxtaposed to the flat portion of the lock bearing in the release position and at least
7 one of the annular teeth being in the slot in the lock position.

SUBA2

2 52. A method of storing a tray stack having a plurality of individual trays
3 carrying microelectronic devices, the tray stack having a first exterior tray at one end of
4 the tray stack and a second exterior tray at an opposite end of the tray stack, the method
5 comprising:

6 inserting the tray stack along a load/unload path into a casing of a tray
7 retaining device until the first exterior tray contacts a cross-member of the tray retaining
8 device;

9 restricting the individual trays from moving laterally with respect to the
10 load/unload path; and

11 selectively impeding movement along the load/unload path in a first
12 direction by moving a retaining element attached to the tray retaining device from a
13 load/unload position to a storage position, the retaining element allowing the tray stack to
14 move along the load/unload path in the load/unload position and the retaining element
15 engaging the second exterior tray in the storage position to impede movement of the tray
stack along the load/unload path in a second direction.

1 53. The method of claim 52 wherein inserting the tray stack comprises
2 positioning the retaining element in the load/unload position and sliding the tray stack
3 along the load/unload path and into the casing.

SUB A2

54. The method of claim 52 wherein inserting the tray stack comprises
2 attaching the tray retaining device to a processing station of a processing machine by
3 positioning the retaining element in the load/unload position in which the retaining
4 element engages a mounting element of the processing station and sliding the tray stack
5 along the load/unload path and into the casing.

55. The method of claim 52 wherein:

2 the cross-member is a floating plate that is moveable along the load/unload
3 path in the casing;

4 inserting the tray stack comprises attaching the tray retaining device to a
5 processing station of a processing machine by positioning the retaining element in the
6 load/unload position in which the retaining element engages a mounting element of the
7 processing station and sliding the tray stack along the load/unload path and into the
8 casing, the floating plate moving in the first direction; and

9 the method further comprises preventing the floating plate from moving
10 when the retaining element is in the storage position and allowing the floating plate to
11 move when the retaining element is in the load/unload position.

56. A method of storing a tray stack having a plurality of individual
2 JEDEC trays carrying microelectronic devices, the tray stack having a first exterior tray at
3 one end of the tray stack and a second exterior tray at an opposite end of the tray stack,
4 the method comprising:

5 providing a portable tray retaining device configured to hold the stack of
6 JEDEC trays, the tray retaining device including a casing, a plurality of retaining
7 elements coupled to the casing and a driving element moveably coupled to the casing,
8 wherein the casing includes a guide structure with a first end and a second end, a cross-
9 member extending across at least a portion of the guide structure at least proximate to the
10 first end, and an opening at least proximate to the second end through which the JEDEC
11 trays can pass into or out of the casing, wherein the retaining elements are moveable

Sub A2
12 between a storage position and a load/unload position, the retaining elements projecting
13 into the guide structure in the storage position to hold the JEDEC trays in the retainer,
14 and the retaining elements projecting away from the guide structure in the load/unload
15 position to allow the JEDEC trays to pass through the opening, and wherein the cross-
16 member is moveably coupled to the casing to move along a load/unload path to push the
17 tray stack toward the second end of the casing;

18 inserting the tray stack along the load/unload path into the casing; and
19 moving the retaining elements from the load/unload position to the storage
20 position in which the retaining elements engage the second exterior tray and the cross-
21 member engages the first exterior tray to restrict movement of the tray stack along the
22 load/unload path.

23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57. The method of claim 56 wherein inserting the tray stack comprises
58 positioning the retaining element in the load/unload position and sliding the tray stack
59 along the load/unload path and into the casing.

60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
220

9 the method further comprises preventing the floating plate from moving
10 when the retaining element is in the storage position and allowing the floating plate to
11 move when the retaining element is in the load/unload position.

1 60. A method of processing microelectronic devices in a tray stack
2 having a plurality of individual trays carrying the microelectronic devices, the tray stack
3 having a first exterior tray at one end of the tray stack and a second exterior tray at an
4 opposite end of the tray stack, the method comprising:

5 inserting the tray stack along a load/unload path into a casing of a tray
6 retaining device until the first exterior tray contacts a cross-member of the retaining
7 device, the casing being configured to restrict the individual trays from moving laterally
8 with respect to the load/unload path;

9 moving a retaining element attached to the tray retaining device from a
10 load/unload position to a storage position, the retaining element allowing the tray stack to
11 move along the load/unload path in the load/unload position and the retaining element
12 engaging the second exterior tray in the storage position to restrict movement of the tray
13 stack along the load/unload path;

14 releasably attaching the tray retaining device to the receiving station of the
15 processing machine;

16 releasing the tray stack to move along the load/unload path by moving the
17 retaining element from the storage position to the load/unload position to disengage the
18 retaining element from the second exterior tray of the tray stack; and

19 separating individual trays from the tray stack and processing the
20 microelectronic devices on the individual trays in the processing machine.

1 61. The method of claim 60 wherein releasably attaching the tray
2 retention device to the receiving station occurs when the retaining element moves from
3 the storage position to the load/unload position by engaging the retaining element with a
4 mounting element attached to the processing machine.

SUB 1
A2 2

62. The method of claim 60 wherein inserting the tray stack comprises positioning the retaining element in the load/unload position and sliding the tray stack along the load/unload path and into the casing.

63. The method of claim 60 wherein:
the cross-member is a floating plate that is moveable along the load/unload path in the casing; and
the method further comprises preventing the floating plate from moving when the retaining element is in the storage position and allowing the floating plate to move when the retaining element is in the load/unload position.

10035375-100401
Add B47